ViewSonic®

VG151 LCD Display

ViewPanel® Series

- **OPTISYNC BEYOND DIGITAL technology**
  This multi-mode input technology supports both digital (DVI) and analog (VGA) signals. The digital interface delivers optimized image quality with minimum adjustments.
- **Full 15" screen**
  The VG151 displays a full, flat 15.0" viewable area that is larger than the viewable area of traditional 15" (various viewable) CRTs.
- **1024 x 768 maximum resolution**
  Displays a crisp, clear native resolution of 1024 x 768 for easy-on-the-eyes viewing. Automatically scales lower resolutions to fill the screen.
- **OSD / Power Lock**
  Prevents accidental misadjustment of OnView® controls to maintain optimized image quality.
- **OnView® controls**
  All screen adjustments are made via an on-screen menu with user-friendly four-button navigation.
- **Slim 2.3" profile (panel only)**
- **Weighs only 10.6 pounds**
- **VESA® wall mountable (75mm) capability***

15.0" TFT LCD display with OptiSync™ technology.

The VG151 represents state-of-the-art performance. Taking only a fraction of the space used by a comparable-size CRT, the VG151 offers users a full 15" viewable screen. It's portable enough to move quickly and easily with its 2.3" profile, 10.6 pounds and wall mount capability. For professionals who need the latest digital computer technology, the new OptiSync feature with digital and analog inputs is also included. What's more, its anti-static, anti-glare screen highlighting a 1024 x 768 true resolution, is very easy on the eyes. With all these features the ViewSonic VG151 is a great 15" flat panel any way you look at it.

ViewSonic®
See the difference.®

ViewSonic®

VG151 LCD Display

VG151b black case version

- **ViewSonic Wizard**
  Automates the installation and optimization of your ViewSonic monitor. The included CD-ROM contains the ViewSonic Wizard, color management software and a multi-lingual user guide.
- **Anti-static, anti-glare screen**
  This screen treatment minimizes reflections while maintaining the highest image quality.
- *Plug & Play+*
- **TCO '99 and ENERGY STAR® certified**
- **PC and Mac® compatible****
- **Kensington® security port**
  Kensington security port protects your assets.
- **Three-year limited warranty**

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

15.0" TFT LCD DISPLAY WITH OPTISYNC™ TECHNOLOGY

LCD	**Type**	TFT active matrix LCD (16.7 million colors)
	Display Area	15.0" viewable
	Contrast Ratio	350:1 (typ)
	Viewing Angle	120° horizontal, 100° vertical (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Response Time	40ms (typ)
	Brightness	210 cd/m² (typ)
	Glass Surface	Anti-static, anti-glare coat
VIDEO INPUT	**Video**	RGB analog or DVI-D digital
	Frequency	F_h:30-62kHz, F_V:50-75Hz
ANALOG	**Sync**	H/V Separated (TTL) composite, sync on green
COMPATIBILITY	**PC**	VGA up to 1024 x 768 non-interlaced
	Mac®**	Power Mac™ up to 1024 x 768
CONNECTORS	**Analog RGB**	15-pin mini D-sub
	Digital Input	24-pin DVI-D
	Power	Adapter with 3-pin AC plug (CEE22), DC to head
	Security	Kensington® security port
POWER		AC 100-240 VAC, 50/60Hz (auto switch), 20W (typ)
USER CONTROLS	**Basic**	1, down arrow, up arrow, 2, power
	OnView®	Auto contrast, contrast, brightness, H/V-position, H-size, auto sync, fine tune, ViewMatch® color, input select (analog/digital), ViewMeter®, OSD position, OSD language, smoothing, recall, background
BANDWIDTH	**Pixel Clock**	100Mhz (max)
DISPLAY AREA		304mm (H) x 228mm (V)
DIMENSIONS	**Physical**	390mm (W) x 372mm (H) x 167mm (D) (15.3" x 14.6" x 6.6")
WEIGHT	**Net**	4.8kg (10.6 lbs.)
OTHER		DDC1 & DDC2B
REGULATIONS		UL, FCC-B, ENERGY STAR®, DOC-B, CE, Energy 2000, CSA, CB, TCO '99, TUV/GS, NEMKO, SEMKO, DEMKO, FIMKO, BSMI, VCCI, CCIB, CCEE, PCT, C-TICK, B-MARK, TUV/ERGO
POWER MANAGEMENT		Meets ENERGY STAR®, VESA® DPMS, TCO '99 (VG151b - TCO '95) and Energy 2000 standards
WARRANTY		Three-year limited warranty on parts, labor and back light.

ViewSonic®
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 • Phone (800) 888-8583 or (909) 444-8888 • Fax (909) 839-7922 • E-mail: SalesInfo@ViewSonic.com • ViewSonic.com

*Wall mount accessories are optional. Designed for easy wall mount configuration with any optional third-party wall mount kit to meet VESA wall mount specifications. **Free universal Mac® adapter available. The EPA only promotes energy efficiency and does not endorse any particular company or product. Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2001 ViewSonic Corporation. All rights reserved. [10308-02B_09/01_5m] VS-2228